S9056RT-HC/S9070RT-HC

ULTRA-HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS



- Ultra-high capacity, large deck rough terrain scissor lifts
- Excellent rough terrain performance
- Heavy duty design
- Dual powered extension decks
- Ideal for construction applications



ULTRA-HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS


DIMENSIONS	\$9056RT-HC*	\$9070RT-HC*	
Max. working height	62 ft	76 ft	
Max. platform height (A)	56 ft	70 ft	
Platform size (stowed)	18 ft x 7 ft 4 in		
Platform size (extended)	27 ft x 7 ft 4 in		
Extension deck length	4 ft 8 in		
Overall width (B)	7 ft 6 in		
Overall length (C)	18 ft		
Stowed height (D)	10 ft 2 in	11 ft 3 in	
Min. height (guardrails folded)	7 ft	8 ft 5 in	
Ground clearance		9 in	

PERFORMANCE			
Platform capacity (SWL)	3,000 lbs	2,000 lbs	
Max. drive height		43 ft	
Max. wind speed	28 mph		
Max. drive speed (stowed)	4 mph		
Max. drive speed (elevated)		0.3 mph	
Raise/lower time	63/58 sec	98/78 sec	
Gradeability		50%	
Max. stabilizer levelling, front to rear		7°	
Max. stabilizer levelling, side to side		12°	
Inside turning radius	8 ft		
Outside turning radius		18 ft 6 in	
Tires	13 x 36 foam filled		
Controls	propo	proportional joystick	
Drive system	4-wheel drive		


POWER	
Power source	Kubota diesel

WEIGHT		
Weight	20,000 lbs	25,500 lbs

TURNING RADIUS



S9056RT-HC/ S9070RT-HC



STANDARD FEATURES

- 4-wheel drive
- 4 hydraulic stabilizers with automatic levelling
- Dual powered extension decks
- Proportional controls
- Foam filled tires
- Power line to platform
- Platform overload system
- Drive motion alarm
- Descent alarm
- Locking, oscillating axle
- Fold-down guardrails
- Manual lowering valve
- Flashing amber light (x2)
- Dual lanyard attachment points
- Hour meter & on-board diagnostics display
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

OPTIONS

- Special paint colors
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Dual fuel
- Non-marking foam filled tires
- Cold weather package (block heater + battery blanket)
- Hydraulic 110V 2kW generator
- 12kW generator package



P.O. Box 1160

St.Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000

Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com