TM12E / TM16E / TM20E



ELECTRIC DRIVE MAST LIFTS



- Smooth & efficient electric drive
- Zero inside turning radius
- Versatile, robust and easy-to-use
- Drives through standard doorway
- Compact & easy to maneuver
- Ideal for many applications from construction to stockpicking



ELECTRIC DRIVE MAST LIFTS


DIMENSIONS	TM12E	TM16E	TM20E	
Max. Working Height	18′	22′	25′ 9″	
Max. Platform Height (A)	12′	16′	19′ 9″	
Platform Size (Stowed)	27" x	27" x 39"		
Platform Size (Extended)	27" x	27" x 59"		
Deck Extension Length	20	20"		
Overall Length (C)	4′ 6″			
Overall Width (D)	2′ 6″	2′ 6″		
Stowed Height (B)	5′ 6″		6′ 6″	
Ground Clearance (Stowed)	3"		2.85"	

PERFORMANCE				
Platform Capacity (SWL)	500 lbs 45			450 lbs
Max. Drive Height	12′		16′	19′ 9″
Max. Wind Speed	28 mph		0 mph	
Max. Drive Speed (Stowed)		2.5 mph		2.8 mph
Max. Drive Speed (Elevated)	0.4 mph 0.5 m			0.5 mph
Gradeability	25%			
Max. Operating Slope (side-to-side)) 2°		1.5°	
Max. Operating Slope (front-to-bac	ck) 2°		1.5°	
Inside Turning Radius		()"	
Outside Turning Radius	55.5"		54"	
Raise/Lower Time	19 / 17 sec	28 / 36	sec	24 / 26 sec
Tires	12.7 non-marking rubber			
Controls	Proportional joystick			
Drive System	Dual DC motors			
Parking Brake	2-wheel, spring-applied, electric release			


POWER	
Power Source	24V 220Ah batteries
Charger	20amp charger

WEIGHT			
Weight	2,240 lbs	2,430 lbs	2,500 lbs

TURNING RADIUS



TM12E / TM16E / TM20E



STANDARD FEATURES

- Zero inside turning radius
- Roll-out deck extension
- Non-marking rubber tires
- Proportional controls
- Platform overload system
- Emergency lowering at chassis controls
- Descent & tilt alarms
- 1 person indoors
- Crane lift points
- Single entry gate
- Hour meter & on-board diagnostic display
- Horr
- Integrated battery charger 110V / 20A
- Selectable motion alarm
- 2-year parts & labor warranty
- 5-year structural warranty

OPTIONS

- Environmental hydraulic oil
- Special paint colors



P.O. Box 1160 St. Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000 Toll-Free: 1 (800) 255-0317 Sales Fax: 1 (785) 989-3070

Parts Fax: 1 (785) 989-3077 Email: sales.usa@snorkellifts.com